



ALL DIMENSIONS IN MM. TOLERANCES ARE +0.3MM.

22	K	POWER SUPPLY FOR BACKLIGHT(-)
21	A	POWER SUPPLY FOR BACKLIGHT(+)
20	NC	NO CONNECT
19	VEE	NEGATIVE VOLTAGE
18	FS	FONT SELECTION
17	DB7	DATA BUS
16	DB0	
15	DB0	
9	RES	RESET SIGNAL
8	C/D	COMMAND/DATA SELECTION
7	CE	CHIP ENABLE
6	RD	DATA READ FROM T6963C
5	WR	DARA WEITE INTO T6963C
4	VO	OPERATING VOLTAGE FOR LCD
3	VDD	POWER SUPPLY (+5.0V)
2	VSS	POWER SUPPLY (GND)
1	FG	FRAME GRDUNG
NO.	SYMBOL	DESCRIPTION

DM128128A	NO.	TOTAL:
PART NO.	REV	A
DESIGN		
CHECK		
APPROVE		

NOTES:

- LCD DISPLAY TYPE : STN,YELLOW-GREEN
- POLARIZER TYPE : TRANSPARENT, POSITIVE
- DRIVING VOLTAGE : 18.0V
- VIEWING ANGLE : 6:00
- DUTY : 1/128
- BIAS : 1/12
- OPERATING TEMPERATURE : 0°C-50°C
- STORAGE TEMPERATURE : -10°C-60°C
- LOGIC VOLTAGE : 5.0V
- BACKLIGHT MODE: BOTTOM
- BACKLIGHT COLOR : YELLOW-GREEN
- IC : T6963C, T6A36, T6A40
- IC PACKING: BONDING

ORIENT DISPLAY CO.,LTD.