



**SPECIFICATION:**

1. DISPLAY TYPE: STN, YELLOW-GREEN MODE, Transmissive 12H
2. DRIVING METHOD:  $V_0=13.2V$ , 1/64 DUTY, 1/9 BIAS
3. LCD CONTROLOR & DRIVER: S6A0107, S6A0108
4. OPERATION TEMPERATURE:  $-20^{\circ}C \sim +70^{\circ}C$   
STORAGE TEMPERATURE:  $-30^{\circ}C \sim +85^{\circ}C$
5. HEADER: TSW-120-05-G-S OR EQUAL.
6. TOLERANCE UNLESS OTHERWISE SPECIFIED:  $\pm 0.2$  mm
7. INTERFACE:

PIN	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
	VSS	VDD	VEE	RS	R/W	E	DB0	DB1	DB2	DB3	DB4	DB5	DB6	DB7	CS1	CS2	RST	Vout	A	K



**ORIENT DISPLAY**

DRAWN:

CHECKED:

APP:

LCD NO.:

DATE: Oct. 8 2002

UNITS: MM

DWG NO.: DM12864C1-D-YTXTDW

SHEET 1 OF 1